



FR



- Stable operation under strong light
- Large Fingerprint capture area and high image performance
- RS 485
- Low Power Idle Mode
- Comply with ISO/IEC 19794-2

SLAVE READER

HIGH SECURITY FINGERPRINT & RF READER

Model FR is fingerprint & card reader for connecting with Felix product via RS485, fast speed of verification, Facilitated in Installation, small slave reader not only with indicate LED, but also with voice, you could learn the verification result easily. Support Fingerprint and Card mode.

Technical Specifications

Model	FR
Biometric Measurement	Fingerprint
CPU	320MHz
Material	Optical
Interface	RS485
Attendance Mode	Fingerprint or Card or Fingerprint + Card
Voice Instruction	16-bit Hi-Fi voice & sound indication
Verification Time	< 0.5 second [1:N]
Power Current	80mA for standby; 100mA for working
FRR (False Rejection Rate)	< 1%
FAR (False Acceptance Rate)	< 0.0001%
Power source	12VDC/2A
Operating temperature	-10 to 45 Degree Celsius
Operating humidity	20% - 80%RH
Dimensions (mm)	111 x 52 x 27mm
Weight (kg)	0.3
Quantity/Carton	20 units
Gross weight/carton (kg)	8.5

Optional Function

RF Card - 13.56MHZ Mifare

Fingerprint Slave Reader

Brand: Felix

Model: FR



Available SDK for development