



iF686-GPRS



Wi-Fi
2.4GHz

Face
Fingerprint
Card Access
Password



GPRS: 2G/3G/4G

Backup Battery: 2-3 Hours

**HIGH SECURITY TIME ATTENDANCE
& ACCESS CONTROL**

New model iF686-GPRS is popular in the market with smart design, improved function that support WIFI, access control, bell, battery and RFID. Professional communication port with Wiegand in & out, 2 × relay, NC, NO, alarm, etc. Device could be with smooth keypad to be more humanized. Data managed via TCP/IP, WiFi, and USB host port for data upload/download to avoid the risk of accidental deletion. What's more, friendly software eTime with perfect setting of shifts, rules, employees, departments, etc.

- World-class algorithm, high-speed and accurately identify fingerprint.
- Face/Fingerprint/Pin/Card authentication.
- Suitable for the entrances and exits of office, factory, hotel, school, etc.
- Large capacity, user capacity up to 2,000 & logs capacity up to 200,000.
- 2.8 inches TFT color screen 240x320 pixel.
- TCP/IP + USB Flash Drive Download + USB Communication.
- More helpful function like T9 input method, self-service inquiry, etc.
- Support door control & alarm function.
- USB flash drive for offline data management.
- Multi-language: English, Arabic, French, Spanish, Portuguese, etc.
- Multiple shifts setting.
- Professional T&A software eTime.
- Easy wall-mounting.
- Exact calculation of worked hours / overtime.

Technical Specification

Model	iF686-GPRS
Biometric Measurement	Face & Fingerprint
Face capacity	2,000
Fingerprint capacity	5,000
Log capacity	200,000
CPU	400MHz
LCD display	2.8" TFT color screen 320x240 pixel
Interface	TCP/IP, USB (host and slave), 2 × Relay· Wiegand in & out
Language	English, Arabic, French, Korean, Spanish, Portuguese, etc
Attendance mode	Face + Fingerprint or Face or Fingerprint or Password or Card or Fingerprint+Password or Card+Password or Fingerprint+Card+Password
Voice instruction	16-bit Hi-Fi voice & sound indication
Verification time	< 0.5 second [1:N]
FRR (False Rejection Rate)	< 1%
FAR (False Acceptance Rate)	< 0.0001%
Power source	12VDC/2A
Operating temperature	0 - 45 Degree Celsius
Operating humidity	<90%RH
Dimensions (mm)	175 x 145 x 79.5
Weight (kg)	0.33
Quantity/Carton	10 units
Gross weight/carton (kg)	9.7

Face & Fingerprint Time Attendance

Brand: Felix
 Model: iF686-GPRS
 Software: eTime T&A



Optional Function - RF Card: 13.56MHz Mifare



High Powered DSP Chip Finger Sensor



T9 Input Method Keyboard



TFT Color Screen

Application



Accessories



Interface

