

F-4824-05

DIN RAIL POWER SUPPLY



Product Features

- High efficiency, long life and high reliability.
- Protection: Input fuse/overload/over voltage short circuit.
- Multifunction LED indicators.
- Fit for industrial rail TS35/7.5 or 15
- 100% full load burn-it test.

Description

F-4824-05 is a Din-rail power supply, its main output is 48-54VDC adjustable, 5A. It can be used for various security and automation systems.

Technical Specifications

Model		F-4824-05
INPUT	Voltage Range	190 - 265VAC
	Frequency Range	50 - 60Hz
	Efficiency (Typ.)	>88%
OUTPUT	Voltage (AC Mode)	48-54VDC (Adjustable)
	Rated Current	5A
	Rated Power (Max.)	270W
	Ripple & Noise	<400mVp-p
	Line Regulation	±2%
	Load Regulation	±2%
	Output Channel	3 Channels
PROTECTION	Overload	5.75A ±5% Hiccup mode, recovers automatically after fault condition is removed.
	Over Voltage	60V ±5% Hiccup mode, recovers automatically after fault condition is removed
	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed
ENVIRONMENT	Temperature	Working: -20°C~50°C, Storage: -30°C~80°C
	Humidity	Working: 20-80%RH, Storage: 10-90%RH
LED INDICATOR	Green	ON - AC power supplies
BOX	Dimension(mm)	63 x 124 x 113mm